

WINDOW FILM PERFORMANCE DATA



% Visible Light
Transmission

% Total Solar
Energy Rejection

% Ultraviolet
Protection
(wavelengths
300-380nm)

% Glare
Reduction

% Visible Light
Reflection

CLASSIC™ SERIES	Good heat rejection and enhanced style				
Classic 05	5	44	>99	94	5
Classic 15	18	40	>99	79	5
Classic 30	33	36	>99	63	6
Classic 35	38	35	>99	57	6
Classic 50	60	28	>99	32	7
PINNACLE® SERIES	Superior heat rejection and enhanced style with no signal interference				
Pinnacle 05	5	64	>99	94	5
Pinnacle 15	19	60	>99	78	5
Pinnacle 30	33	56	>99	63	6
Pinnacle 35	38	55	>99	57	6
Pinnacle 40	43	53	>99	51	6
Pinnacle 50	55	50	>99	38	7
STRATOS™ SERIES	Most advanced Hybrid-Matrix™ nano-ceramic technology for maximum heat rejection and enhanced style with no signal interference				
Stratos 15	17	63	>99	80	5
Stratos 30	32	59	>99	63	6
Stratos 35	39	58	>99	56	6
Stratos 40	43	57	>99	52	6
Stratos 50	56	54	>99	37	7
Stratos 70	69	49	>99	21	8
AIR SERIES	Lightly-shaded tint that reduces heat but not visibility				
Air 80	78	43	>99	13	9
UVSHIELD™ SERIES	The highest ultraviolet ray protection in the industry without the look of traditional tint				
UVShield 85	85	16	99.9	6	10



LLumar.com

Data captured using NFRC guidelines and calculated for single pane, 1/4" clear glass. Reported values are taken from representative product samples and are subject to normal manufacturing variances. Actual performance will vary based on a number of factors, including glass type and properties. © 2017 Eastman Chemical Company. FormulaOne®, the FormulaOne® logo, LLumar® and the LLumar® logo are trademarks of Eastman Chemical Company or one of its wholly owned subsidiaries. As used herein, ® denotes registered trademark status in the U.S. only. Printed in U.S.A. (02/17) SP1117

