

WINDOW FILM PERFORMANCE DATA

FORMULAONE
WINDOW TINT



% Visible Light
Transmission

% Total Solar
Energy Rejection

% IR Energy
Rejection (IRER)*

% Selective
IR Rejection
(SIRR)**

% Ultraviolet
Protection
(wavelengths
300-380nm)

% Glare
Reduction

% Visible Light
Reflection

CLASSIC™ SERIES

Good heat rejection and enhanced style with no signal interference

Classic 05	5	44	22	29	>99	94	5
Classic 15	18	40	22	29	>99	79	5
Classic 30	33	36	22	29	>99	63	6
Classic 35	38	35	22	29	>99	57	6
Classic 50	60	28	22	29	>99	32	7

PINNACLE® SERIES

Superior heat rejection and enhanced style with no signal interference

Pinnacle 05	5	64	62	90	>99	94	5
Pinnacle 15	19	60	62	89	>99	78	5
Pinnacle 25‡	25	58	60	87	>99	71	5
Pinnacle 30	33	56	61	88	>99	63	6
Pinnacle 35	38	55	61	88	>99	57	6
Pinnacle 40	43	53	61	88	>99	51	6
Pinnacle 50	55	50	61	88	>99	38	7

STRATOS™ SERIES

Most advanced Hybrid-Matrix® nano-ceramic technology for maximum heat rejection and enhanced style with no signal interference

Stratos 15	17	63	66	95	>99	80	5
Stratos 30	32	59	66	96	>99	63	6
Stratos 35	39	58	67	97	>99	56	6
Stratos 40	42	57	67	97	>99	52	6
Stratos 50	56	54	67	97	>99	37	7
Stratos 70	69	49	66	96	>99	21	8



AIR SERIES

Virtually invisible Ceramic protection against heat and harmful UV rays (Clear)

Air 80	77	43	60	86	>99	13	9
--------	----	----	----	----	-----	----	---

EASTMAN

LLumar.com

‡Based on data obtained during product development and is subject to change. *IRER is a more complete measurement of heat experienced from solar infrared radiation (780-2500nm) including absorbed and re-radiated energy. **SIRR is a measurement of solar infrared radiation (78 0-2500nm) not directly transmitted through glass. Data captured using National Fenestration Rating Council's (NFRC) guidelines and calculated for single pane, nominal 1/4 inch (6mm) clear glass. Reported values are taken from representative product samples and are subject to normal manufacturing variances. Actual performance will vary based on a number of factors, including glass type and properties. ***These are calculated numbers which may differ between similar products due to averaging and rounding. See LLumar.com for technical details. ©2019 Eastman Performance Films, LLC. Product brands referenced herein with a ™ or ® symbol are trademarks of Eastman Chemical Company or its subsidiaries. All other trademarks are the property of their respective owners. All rights reserved. No liability is accepted for errors. Printed in U.S.A. (11/19) SP1117

